

501 Waterford, C Wing, C.D.Barfiwala Marg(Juhu Lane), Andheri(W), Mumbai 400 058. INDIA

Email tcmktg@sarex.com URLwww.sarex.com

PRODUCT LITERATURE

FABCOAT-5300

Product Information

Fabcoat-5300 is a Polyurethane base coating, recommended as a coating compound for outdoor fabrics like cordura, , medical cover all fabrics, Umbrella and Bag line fabrics. It forms a clear films. To obtain high water column, two coating of Fabcoat-5300 is recommended.

Key Features & Benefits

Key Features Benefits

Easy to coat Forms clear and tack free films

High water Column Efficient water proofing

High solid Higher add on can be achieved

General Characteristics

Physical appearance : White Liquid

Miscibility : Miscible with water

Compatibility : Compatible with anionic and nonionic

products

Stability : Stable to dilute alkalies and dilute acids

Application

Suggested Recipe:

Fabcoat-5300 : 50-70 Parts
Water : 45-25 Parts
Saraprint-AC : 3-5 Parts

Thickener : To adjust desired viscosity

- Pre-impregnation with flourocarbon is recommended before coating
- Fabcoat-5300can be applied by knife on air
- Curing should be done at 160 deg.C for 3 mins



501 Waterford, C Wing, C.D.Barfiwala Marg(Juhu Lane), Andheri(W), Mumbai 400 058. INDIA

Email tcmktg@sarex.com URLwww.sarex.com

PRODUCT LITERATURE

FABCOAT-5300

- For achieving high add-on, Fabcoat-5300should be coated in 2 pass
- In case of high water repellency requirement, the fabric must be post impregnated with flourine containing water repellent

Precautions

Storage : Store in cool, ventilated shed away from

heat and direct sunlight. Storage temperature should not exceed 35 deg C. Close lids firmly to avoid contact with air and moisture.

Shelf Life : 9 months from the date of manufacturing, if

stored under controlled conditions.

[The above information is given in good faith and is without warranty] Prod.Code :L010234.docx | Last Upd. On : 22/05/20] [PP]

This is a computer generated report. Hence not signed.