

501 Waterford, C Wing, C.D.Barfiwala Marg(Juhu Lane), Andheri(W), Mumbai 400 058. INDIA

Email tcmktg@sarex.com URLwww.sarex.com

PRODUCT LITERATURE

TEXPEACH-RSL

Product Information

Texpeach-RSL is an Anti pilling finishing agent for all types of fabric, specially good for linen fabric. It improves the resistance of treated fabric to pilling, snagging and also reduces the tendency of seam slippage. It also acts as an Anti-slipping agent for fibres in order to avoid yarn slippage. Texpeach-RSL can be applied by exhaust as well as pad application. Fabric finish with Texpeach-RSL increases the use of velcro strip fastner. It gives resistant to washing and dry cleaning. Does not affect the hydrophilic property of finished fabric, does not make fabric harsh gives very soft feel.

Key Features & Benefits

Key Features Benefits

Multifunctional Anti-pilling, Anti-slip and

Anti-snag finish can be developed

- Improves Velcro resistance

Versatile - Suitable for all substrates, specially for Linen

- Applicable by padding and exhaust method

No entanglement Keeps the fabric surface free from pills

General Characteristics

Physical appearance : Straw White to Off White liquid Ionic nature : Nonionic to Weekly Cationic

pH of 1% solution : 5 +/-1

Miscibility : Miscible with water

Compatibility : Compatible with cationic and nonionic products
Stability : Stable to dilute acids and unstable to dilute alkalies

Application

Padding process Exhaust process
----Dosage: 20-30 g/1 Dosage: 2-3%

501 Waterford, C Wing, C.D.Barfiwala Marg(Juhu Lane), Andheri(W), Mumbai 400 058. INDIA

Email tcmktg@sarex.com URLwww.sarex.com

PRODUCT LITERATURE

TEXPEACH-RSL

Pick-up: 65-70% Bath pH: 5.0-6.0

Bath pH : 5.0-6.0 Bath Temp.: 30-40 deg.C

Note:

- Shake well and use

- To achieve better results at higher revolutions, higher concentration of Texpeach-RSL recommended.

- Pre lab trials recommended.

Precautions

Storage : Store in cool, ventilated shed away from

heat and direct sunlight. Storage temperature should not exceed 35 deg C. Close lids firmly to avoid contact with air and moisture.

Shelf Life : 9 months from the date of manufacturing, if

stored under controlled conditions.

[The above information is given in good faith and is without warranty] [Prod.Code :L011221 | Last Upd. On : 18/05/23] PVR]

This is a computer generated report. Hence not signed.