

501 Waterford, C Wing, C.D.Barfiwala Marg (Juhu Lane), Andheri(W), Mumbai 400 058. INDIA

Phone - +91 22 42184218 **Fax** +91 22 42184350 Email tcmktg@sarex.com URL www.sarex.com

PRODUCT LITERATURE **CAREGUARD-7321**

Product Information

Careguard-7321 is a high performance but cost effective C 6 based Oil and water repellent. Careguard-7321 is made from a new high performance monomer hence giving outstanding performance though at very completive prices. It confers excellent Oil repellency and very good water repellency on all substrates. It can be applied by padding, foaming and by spray technique. For enhanced durability addition of Ecolink (CONC) is recommended.

Key Features & Benefits

Key Features Benefits

Made from speciality monomer High performance Durable Water Repellency and Oil Repellency.

Universal Suitable on all substrates

Low Unit Price Cost effective solution

General Characteristics

Physical appearance Creamish liquid

Ionic nature Cationic pH of 1% solution 5 +/- 1

Miscibility Miscible with water

Compatible with cationic & nonionic products Compatibility

Stability Stable to dilute acids & dilute alkalies

Application

Pick-up : 65-70% Bath pH : 4.0-4.5

Drying : 100-120 deg.C

: 150 deg.C, 5 min. OR 160 deg.C, 3 min. OR 170 deg.C, 1 min Curing

SUGGESTED RECIPES:

For all substrates:

Careguard-7321 : 30-100 g/l Acetic Acid : 0.5 g/l **IPA** 5 g/l

Document: L010535.docx

Concentration of Careguard-7321 to be taken on the basis of durability requirement.

[The above information is given in good faith and is without warranty]

This is a computer generated report. Hence not signed.

Page: 1 of 2

Last Updated on: 30-01-2025 15:14

Pai

Printed by :Jeevanprabha



501 Waterford, C Wing, C.D.Barfiwala Marg (Juhu Lane), Andheri(W), Mumbai 400 058. INDIA

Phone - +91 22 42184218 **Fax** +91 22 42184350 Email tcmktg@sarex.com URL www.sarex.com

PRODUCT LITERATURE **CAREGUARD-7321**

Note:

It is recommended to prewash the substrate to be treated with 1 g/l Saragen-DAM at 80-85 deg.C for 20-30 min. To remove traces of residual impurities to get excellent results.

- 1. After padding and drying if fabric is kept overnight before curing, results will be further improved.
- 2. Water-oil repellent finish can be combine with resin finish using 30 g/l Saralink-ULF + 6 g/l MgCl2 + 20 g/l Saralube-2975.

Sequence of addition:

- Prepare bath with all ingredients including Saralink-ULF, MgCl2 in water containing Acetic acid.
- Stir continuously and add Careguard-7321 as the final ingredient.

Precautions:

- Avoid high speed and continuous stirring.
- Avoid silicone based softeners in the finishing recipe.

Precautions

Storage Store in cool, ventilated shed away from heat and direct sunlight. Storage

temperature should not exceed 35 deg c. Close lids firmly to avoid contact with air

and moisture.

Shelf Life 9 months from the date of manufacturing, if stored under controlled conditions.

[The above information is given in good faith and is without warranty]

This is a computer generated report. Hence not signed.

Last Updated on: 30-01-2025 15:14

Pai

Document: L010535.docx

Printed by :Jeevanprabha

Page: 2 of 2