501 Waterford, C Wing, C.D.Barfiwala Marg(Juhu Lane), Andheri(W), Mumbai 400 058. INDIA

Email:tcmktg@sarex.com URL www.sarex.com

PRODUCT LITERATURE

TEXWHITE-SFN.

Product Information

Texwhite-SFN. is fluorescent whitening agent with bluish violet tone for polyester and polyester blends at all stages of processing. It is suitable for continuous and exhaust processes. Texwhite-SFN. is a very economical and even small application can produce a brilliant white effect of a very high standard.

Key Features & Benefits

Key Features Benefits

Medium to high affinity & Suitable for continuous processes wide pH range application Outstanding leveling properties in

exhaust processes

Stable to wide pH (3-9)

Fabric texture not affected Low temperature curing

Excellent build-up Very high and brilliant white

maximum in continuous and exhaust

applications

Good stability to alkali, Stable in hydrogen peroxide and peroxide and electrolyte sodium hypochlorite bleaching and also to reducing agents liquors and also in reductive

bleaching liquors

General Characteristics

Physical appearance : Greyish liquid

Ionic nature : Nonionic
pH of 1% solution : 6 +/- 1

Miscibility : Miscible with water

Compatibility : Compatible with anionic, cationic and

nonionic products

Stability : Stable to dilute acids and dilute alkalies

Application

Padding process:



Email:tcmktg@sarex.com URL www.sarex.com

PRODUCT LITERATURE

TEXWHITE-SFN.

Dosage : 1-5 g/l (depending on substrate quality)

Pick-up : 65-70% Bath pH : 5.0-6.0

Thermofix: 170-210 deg.C, 45-60 secs.

Exhaust process:

Dosage : 0.1-0.5% (depending on substrate quality)

Bath pH : 5.0-6.0 Bath Temp.: 95-130 deg.C Time : 20-30 mins.

STABILITY & FASTNESS PROPERTIES:

Fastness properties

Methods

change in degree
of whiteness

Light fastness

Light fastness

ISO 105-B02

5 - 6

Wash fastness, 60 deg.C

ISO 105-C06 C1

Sush fastness, 90 deg.C

Dry heat fixation, 180 deg.C

Dry heat fixation, 210 deg.C

Perspiration, acidic

Perspiration, alkaline

Methods

Change in degree
of whiteness

5 - 6

Whiteness

5 - 6

Sush fastness

Fixo 105-B02

Sush fastness

Fixo 105-B04

Fixo 105-B04

Precautions

Storage : Store in cool, ventilated shed away from

heat and direct sunlight. Storage temperature should not exceed 35 deg C.Close lids firmly to avoid contact with air and moisture.

Shelf Life : 9 months from the date of manufacturing, if

stored under controlled conditions.



501 Waterford, C Wing, C.D.Barfiwala Marg(Juhu Lane), Andheri(W),Mumbai 400 058. INDIA

Email:tcmktg@sarex.com URL www.sarex.com

PRODUCT LITERATURE

TEXWHITE-SFN.

[The above information is given in good faith and is without warranty] [Prod.Code :PT483 | Last Upd. On : 05/11/14] [MOLL]

This is a computer generated report. Hence not signed.